

## **Ecodesign EU Declaration of Conformity**

DoC Scan-Line 550 insert RRF-29 08 1700-2008 **Product fiche** 



Manufacturer	Heta A/S
Adress	Jupitervej 22, DK 7620 Lemvig
E-mail	heta@heta.dk
Website	www.heta.dk
Telephone	+45 9663 0600

Model identifier | Scan-Line 550 Insert

The identified product described above is in conformity with:		
The relevant EU harmonized regulations:		
DIR 2009/125/EF		
REG (EU) 2015/1185		
REG (EU) 2015/1186		
REG (EU) 2017/1369		
REG (EU) 305/2011		
The relevant harmonized standards		
EN 13229:2001/A1:2003/A2:2004		
CEN/TS 15883:2010		

Characteristics when operating with the preferred fuel only				
Heat output				
Item	Symbol	Value/Unit		
Nominal heat output	P <sub>nom</sub>	5,3 kW		
Minimum heat output	P <sub>min</sub>			
Useful efficiency (NCV as received)				
Useful efficiency at nominal heat output	$\eta_{ ext{th, nom}}$	81,7%		
Useful efficiency at minimum heat output	η <sub>th, min</sub>			
Auxiliary electricity consumption				
At nominal heat output	el <sub>max</sub>	- kW		
At minimum heat output	el <sub>min</sub>	- kW		
In standby mode	el <sub>sв</sub>	- kW		

Type of heat output/room temperature control		
single stage heat output, no room temperature control	Yes	
two or more manual stages, no room temperature control	No	
with electronic room temperature contro	No	
with electronic room temperature control	No	
with electronic room temperature control plus day timer	No	
with electronic room temperature control plus week timer	No	

Other control options	
room temperature control, with presence detection	No
room temperature control, with open window detection	No
with distance control option	No

Notified body relevant to the assessment and verification of constancy of performance

RRF Rhein-Ruhr feuerstätten Prüfstelle GmbH. 46047 Oberhausen, Deutschland Notified body No. NB 1625 Report nr. RRF-29 08 1700

Fuel	Preferred fuel	Other suit- able fuel
Wood logs with moisture content ≤ 25 %	Yes	No
Compressed wood with moisture content < 12 %	No	No
Other woody biomass	No	No
Non-woody biomass	No	No
Anthracite and dry steam coal	No	No
Hard coke	No	No
Low temperature coke	No	No
Bituminous coal	No	No
Lignite briquettes	No	No
Peat briquettes	No	No
Blended fossil fuel briquettes	No	No
Blended biomass and fossil fuel briquettes	No	No
Other blend of biomass and solid fuel	No	No

Emissions at		mg/Nm³ (13 % O <sub>2</sub> )			
nominal heat output	<b>η</b> <sub>s</sub> %	PM	OGC	СО	NO <sub>x</sub>
output	≥ 65	≤ 40	≤ 120	≤ 1500	≤ 200
	71	25	64	1000	120

Technical documentation	
Indirect heating functionality:	No
Direct heat output:	5,3 kW
Energy Efficiency Index (EEI):	EEI 108
Fluegas temperature at nominal heat output	T 232°C
Energy efficiency class	<b>A</b> ⁺

Safty	
Reaction to fire	A1
Test of fire safety in connection with the burning of wood	Approved
Distance to combustible materials Rear. With insulation Sides distance to combustible materials Furniture distance	Minimum distances in mm # # 800

# See Clearances for installation in instructions

Signed on behalf the manufacturer of 04.05.2022

// Heta //s	
JUPITERYEJ 22 - DK-7620 LEMVIG	
TLF: +45 9663 9600 - FAX +45 9663 0616	S
Martin Bach 10 0010	•

The chimney sweep's signature	Date
Signature	